

Catalog Card Intercom In-02



Sat-System Sp. z o.o.
Ul. Stanisława Staszica 47
05-092 Łomianki
Tel: +48 22 888 99 01
Mail: biuro@teletechnika.pl
www: www.teletechnika.pl



ISO 9001:2015



IST/TS 22163:2017



AQAP 2110:2016



Świadcetwo
Bezpieczenstwa
Przemysłowego



Ministerstwo
Spraw Wewnętrznych
i Administracji

PURPOSE, DEVICE CHARACTERISTICS

Intercom In-02 is a device intended for use both indoors and outdoors. The housing is IP-65 tight. Durable IK10 housing provides the highest resistance to damage and acts of vandalism. Thanks to the use of the SIP 2.0 protocol, it can be used both individually and in extended systems. Based on full duplex communication ensuring high quality of connections with the operator panel.

TECHNICAL DATE

Technical parameters	
Dimensions	108x162x30
Libra	0,75kg
Case	Made of corrosion-resistant material - Aluminum
Housing tightness	IP-57
Protection level	IK-10
Operating temperature range	-10°C do +60°C; humidity 10%-95% noncondensing
Supply voltage	DC12V, 1.5A: PoE (IEEE 802.3af)
Speaker power	2W
Sound features	G.711 a/u; G.729; G.723.1; SIP Info
Protocols	SIP 2.0 (RFC3261, RFC3262); IAX2
LAN	DHCP; PPPoE; VPN (L2TP); NAT; VLAN