

# COUNTER INTERCOM STATION WITH INDUCTION LOOP **HUSAR IKPI**



## PRODUCTS IN SERIES HUSAR CT ANS



Scan for more detailed  
information on the met  
standards and tests of  
this product.

- ✓ High-quality intercom station designed for use at counter's windows
- ✓ Induction loop amplifier included to allow people using hearing aids to hear and carry on a conversation with the system operator
- ✓ Noise and crackle blocking feature provides clear and crisp sound
- ✓ Automatic detection of operating status and automatic signal correction
- ✓ Full duplex operation
- ✓ Master and slave volume control from the touch panel on the microphone panel

## TECHNICAL DATA OF COUNTER INTERCOM STATION WITH INDUCTION LOOP **HUSAR IKPI**

Technical parameters	
Intercom	full duplex
Volume adjustment	Separately for master and slave station
Master station dimension	160mm × 90mm × 42mm
Slave station dimension	Ø 90mm × 22mm
Master audio	2W, microphone sensitivity 36dB
Slave audio	3W, microphone sensitivity 58dB
Power supply	DC 12V
Power consumption	≥6W

This data sheet is commercial in nature. If more detailed technical information is required, the reference document is the technical and operating documentation to be obtained from the manufacturer. In addition, the manufacturer reserves the right to make changes regarding the parameters, specifications and characteristics of the product. The dimensions of optional products, manufactured to order, will have different dimensions than those shown in this sheet. The document of general terms and conditions of supply can be found on the manufacturer's website - [www.railway-systems.eu](http://www.railway-systems.eu)

